

What is Claimed Is:

1. A programmable digital filter integrated circuit, comprising:
  - a. a bus;
  - b. a processor, connected to said bus, for performing digital filtering on
  - 5 digital signals; and
  - c. a programmable interface, connected to said bus, for selectively receiving digital signals having different properties for filtering by said processor.
2. The integrated circuit of claim 1 in which said properties include
- 10 data rate.
3. The integrated circuit of claim 1 in which said properties include algorithm by which said digital signals were encoded.
4. The integrated circuit of claim 1 in which said programmable interface includes:
  - 15 a. a data input port;
  - b. a plurality of input latches connected to said input port;
  - c. a multiplexor, having a plurality of inputs, each receiving a respective output from a input latch; for selecting an input latch to be connected to a multiplexor output.
- 20 5. The integrated circuit of claim 4 in which the output of said multiplexor is connected to at least one sinc filter.
6. The integrated circuit of claim 5 in which the output of said multiplexor is connected to two different sinc filters.
7. The integrated circuit of claim 6 in which said two different sinc
- 25 filters can be selectively activated.

8. The integrated circuit of claim 6 in which one of said sinc filters is a 5th order decimate by 8 sinc filter.

9. The integrated circuit of claim 6 in which one of said sinc filters is a 6th order decimate by 2 sinc filter.

5        10. The integrated circuit of claim 5 in which the inputs to said two different sinc filters may be selectively connected to said multiplexor or to a test signal data source.    11. The integrated circuit of claim 4 in which the output of the multiplexor is connected to a first sinc filter and the output of the first sinc filter is connected to a programmable sinc filter.

10        12. The integrated circuit of claim 11 in which said programmable sinc filter comprises selectable combinations of a plurality of sinc filters.

13. The integrated circuit of claim 11 in which said plurality of sinc filters comprise two 4th order decimate by 2 sinc filters, a 5th order decimate by 2 sinc filter, a 6th order decimate by 2 sinc filter and a 4th order decimate  
15 by 3 sinc filter.

14. A method of designing an integrated circuit, comprising the steps of:

- a. providing a bus;
- b. providing a processor, connected to said bus, for performing digital  
20 filtering on digital signals; and
- c. providing a programmable interface, connected to said bus, for selectively receiving digital signals having different properties for filtering by said processor.

15. A method of fabricating an integrated circuit, comprising the steps  
25 of:

- a. providing a bus;

b. providing a processor, connected to said bus, for performing digital filtering on digital signals; and

c. providing a programmable interface, connected to said bus, for selectively receiving digital signals having different properties for filtering by  
5 said processor.